

General description

- Pure aluminium
- Adhesive : solvent-base acrylic
- Self-adhesive with white paper liner of 70 g / m²
- Excellent peel adhesion
- Good initial tack and permanent bonding
- Outstanding temperature and aging resistance



Technical specification :

	EBA-30	EBA-40	Tolerances	Test method
Width	50 and 75 mm	50 and 75 mm	+/- 3 mm	
Length	50 m	10 and 50 m	+/- 0,3 m	
Aluminium thickness	26 micron	36 micron	+/- 10 %	PSTC-33 / ASTM D3652
Total thickness	60 micron	70 micron	+/- 10 %	PSTC-33 / ASTM D3652
Elongation	3,0 %	3,0 %		PSTC-31 / ASTM D3759
Peel	20 N/25 mm	20 N/25 mm		PSTC-1 / ASTM D3330
Tack	20 cm	20 cm		PSTC-6 / ASTM D3121
Tensile strength	37,5 N/25 mm	50 N/25 mm		PSTC-31 / ASTM D3759
Fire resistance (25/50 & Class 0)	Non classified	Non classified		
Service temperature	-30 / +120 °C	-30 / +120 °C		
Application temperature	+10 / +40 °C	+10 / +40 °C		

Application

Surface should be clean, dry and free of dust and oil.

Storage

In a dry and well ventilated room, protected against dust and direct sun rays and at temperatures between + 10°C and +30 °C. Under these conditions, the adhesive tapes could be stored a minimum of 12 months. Rolls should be stored flat on the slit edge and in their original packaging.