
TECHNICAL DATA SHEET (1/1)

T - 2080 _ PVC TAPE

General description

The **PVC TAPE** is a self-extinguishing soft PVC tape with an agressive pressure sensitive rubber-based adhesive.

- Excellent resistance to abrasion, corrosion and moisture.
- High dielectric strength and mechanical protection.
- Without protective liner.



Technical specification

Width	50 mm
Length	33 m
Thickness	0,15 mm
Tensile Strength	30 N / cm
Adhesion	1,8 N / cm
Elongation at break	170 %
Service temperature	Between 0°C and + 90°C
Flammability	Self-extinguishing
Color	Grey*

* other colors on request

Use

- Electrical insulation
- Cable wrapping
- Various industrial applications

Application

Surface should be clean, dry and free of dust and oil.

Storage

The tapes should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Storage temperature should be between +10°C and +25°C. Under these conditions, PVC Grey Tapes could be stored for minimum 12 months.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.