TECHNICAL DATA SHEET (1/1)

T - 2090 _ CLOTH ALU TAPE

General description

The **Adhesive Cloth Tapes**, also called DUCT tape, are composed of a polyethylene coated textile fabric. The inner side is an adhesive rubber. Its use on all connections will increase significantly the air tightness of the ventilation ducting systems.

- Without protective liner
- Also available metalized : ALU DUCT TAPE



Technical specification

Width	50 mm
Length	50 m
Thickness	0,25 mm
Backing	Polyester / cotton
Coating	Polyethylene
Tack	Immediately
Tensile strength	103 N / 25 mm
Adhesion	8 N / 25 mm
Elongation	12 %
Service temperature	-20°C / +50°C (peak at 60°C)
Application temperature	Between -5°C and +35°C
Use	Inside application
Color	Grey

Application

Tapes have to be applied on a clean surface free of dust, grease, moisture and loose matter.
When applied, cut an excess of 10 cm tape to allow overlapping.

Storage

Product needs to be kept in its original packaging in a clean and dry well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of 6 months.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

Climatech International S.A. • BELGIUM • clim@climatech.be • www.climatech.be