TECHNICAL DATA SHEET (1/1)

T - 4660 _ BRA




General description






The suspension brackets are fast, reliable and economical solutions for hanging a duct system.

- Allow easy adapting to all situations and all ducts rectangular or circular mounting.
- They are made out of galvanized steel.
- They are supplied with a rubber damper suitable for a threaded rod of 8 mm or 10 mm. (except BRA-M and BRA T-SP)

Technical specification

	L	Z	U	T-SP	M
					
Height (mm) (± 1 mm)	64	29	35	50	37
Width (mm) (± 1 mm)	50	50	50	58	50
Thickness (mm) (± 0,3 mm)	2	2	2	2	NA
Max. load (kg)	40	40	40	40	1500 N
Suitable for	M8	M8	M8	M8	M10

	L-25	Z-25	W	V
				
Height (mm) (± 1 mm)	95	62	for round ducting	for metal roofing
Width (mm) (± 1 mm)	30	32	30	30
Thickness (mm) (± 0,3 mm)	2,5	2,5	2	2
Max. load (kg)	40	40	40	40
Suitable for	M10	M10	M10	M10

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.