

General description



Support frames are designed to support refrigeration and air conditioning units on flat roofs.

The **BPF 800** set allows a quick and easy set up of a 800 x 500mm frame and the possibility to add one or more **XPF 800** extension in any ways.

Adjustable height between 250mm and 450mm.



Technical specification

	BPF - 800	XPF - 800
		
Contains	• 4 square feet • 4 leg assemblies • 2 side rails • 2 sliding arms • Hardware and end caps	• 2 square feet • 2 leg assemblies • 2 extra large brackets • 2 side rails • 2 sliding arms • Hardware and end caps
Recommended maximum load	150 kg	75 kg
Recommended temperatures	-30°C to +80°C	-30°C to +80°C
Weight structure	20 kg	12 kg
Other :	U.V. resistant	U.V. resistant

Square foot	• Molded feet 200 x 200 mm in high density polyethylene plastic (HDPE) • Pre attached insulating pads • Suitable for 41 x 41 mm rails • Preserves the waterproof membrane of the roof
Height adjustment kit	1. U profile 41mm x 41mm x 2.5mm x 160mm One side closed with hot-dip galvanized M24 square nut. 2. Threaded rod M24 x 250 mm hot dip galvanizing. 3. Hot dip galvanizing support bracket * for base frame: 1 hole diameter 25 mm & 1 hole diameter 11 mm * for extension frame: 1 hole diameter 25 mm & 2 holes diameter 11 mm 4. Three M24 nuts & washers, hot-dip galvanized and to be tightened with a No. 36 wrench, supplied pre-assembled
Side rail	U profile 41 x 21 x 2.5 x 800 mm hot-dip galvanized To be assembled open-side down
Sliding arm	Profile U 41 x 21 x 2.5 x 500 mm with 2 welded open cages on each end To be assembled open-side up

Packaging

- Delivered in one box
(185 x 360 x 1150 mm)



Application

