TECHNICAL DATA SHEET (1/1)

T - 46702 _ IG-621

General description



Acrylic water based polymer sealant.

- Available in buckets of 6 Kg and 1 Kg or in cartridges of 310 ml
- Excellent adhesion to metal.
- Use : airtightness on airduct

Technical specification

Base material	Acrylic water based polymer sealant
Color	Grey
Weight per liter	1,45 Kg
Application temperature	> 0°C
Operation temperature	-30°C / +80°C
Drying time	Few minutes
Ready	24 to 48h
Packaging	Buckets of 6 Kg / buckets of 1 Kg / cartridges of 310 ml
Classification	M1 (non flammable)
	Indoor air confort : A+ french class

Application

Application by brush or spatula on clean, dry and non-greasy surfaces and a temperature of +5 °C to +35 °C.

Read the Material Safety Datasheet

Storage

At 12 months when stored in a dry place at temperatures between +5 °C and +30 °C in its original packaging.

Protect from frost.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.