TECHNICAL DATA SHEET (1/1)

T - 7326 _ G-REL-SS

General description

Circular external louvre for air exhaust or supply made of stainless steel. The louvre is equiped with bird mesh preventing insects and small animals to enter the duct network. The raincap is preventing the water to enter inside the duct. The G-REL-SS is light and easy to install.





Technical description

- Made of stainless steel SS304 - natural color - brushed finish
- Delivered with 1 gasket sealing, 2 stainless steel screws and 1 stainless steel drip nose

Technical specification

Type	A (mm)	B (mm)	C (mm)	D (mm)
G-REL-SS-100	95 ±2	150 ±3	42 ±5	125
G-REL-SS-125	120 ±2	190 ±3	42 ±5	145
G-REL-SS-150	145 ±2	210 ±3	52 ±5	165
G-REL-SS-160	155 ±2	210 ±3	53 ±5	165
G-REL-SS-200	198 ±2	270 ±3	62 ±5	205





Q[1]	Type[2]	100	125	150	160	180	200
30	PS[3]	4					
60		14	9	3			
80		28	9	6	5		
110		53	18	12	8		
130			20	21	10	6	5
190			42	47	15	8	8
220				65	29	11	10
340					66	25	24
430						46	45
570						67	66

[1] Q = Air volume in m³/h
[2]Type = Connection diameter in mm
[3]Ps = Static pressure loss in Pa

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.