

General description

The **Cylindrical Rubber Mounts CG** consist of rubber-metal vibration absorbers, especially indicated for elastic support of airconditioning units and small machines. They protect the environment against the transmission of vibrations, impacts and structural noise.


They are one the most highly evolved series of rubber vibration absorbers, being one of the most complete, safest and offering the best behaviour and stability.



Technical specification

- Manufactured in NR (Natural Rubber) 55°Sh A.
- Natural frequency: 16-14 Hz
- Other hardness available on request
- Other models on request

Description	A (mm)	B (mm)	C (mm)	E (mm)	Deflexion (mm)	Load (Kg)
MMCG 20-20	20	20	M6	20	5	30
MMCG 25-25	25	25	M8	20	6	50
MMCG 25-30	25	30	M8	20	8	50
MMCG 30-30	30	30	M8	20	8	60
MMCG 30-40	30	40	M8	20	9	60
MMCG 40-28	40	28	M8	20	6	120
MMCG 40-40	40	40	M8	25	10	150
MFCG 30-40	30	40	M8	20	9	60
MFCG 40-28	40	28	M8	25	6	120
FFCG 25-25	25	25	M8	20	6	50
FFCG 30-30	30	30	M8	20	7	80



Assembly & application

- Attach the support to the wall
- Fasten the vibration absorbers to the support
- Mount the unit onto the vibration absorbers
- Attach the vibration absorbers onto the holes in the unit

