

**General description**

- Pure aluminium
- Adhesive : solvent-base acrylic
- Self-adhesive with white paper liner of 70 g / m<sup>2</sup>
- Excellent peel adhesion
- Good initial tack and permanent bonding
- Outstanding temperature and aging resistance



**Technical specification :**

	<b>EBA-30</b>	<b>EBA-40</b>	<b>Tolerances</b>	<b>Test method</b>
<b>Width</b>	50 and 75 mm	50 and 75 mm	+/- 3 mm	
<b>Length</b>	50 m	10 and 50 m	+/- 0,3 m	
<b>Aluminium thickness</b>	26 micron	36 micron	+/- 10 %	PSTC-33 / ASTM D3652
<b>Total thickness</b>	60 micron	70 micron	+/- 10 %	PSTC-33 / ASTM D3652
<b>Elongation</b>	3,0 %	3,0 %		PSTC-31 / ASTM D3759
<b>Peel</b>	20 N/25 mm	20 N/25 mm		PSTC-1 / ASTM D3330
<b>Tack</b>	20 cm	20 cm		PSTC-6 / ASTM D3121
<b>Tensile strength</b>	37,5 N/25 mm	50 N/25 mm		PSTC-31 / ASTM D3759
<b>Fire resistance (25/50 &amp; Class 0)</b>	Non classified	Non classified		
<b>Service temperature</b>	-30 / +120 °C	-30 / +120 °C		
<b>Application temperature</b>	+10 / +40 °C	+10 / +40 °C		

**Application**

Surface should be clean, dry and free of dust and oil.

**Storage**

In a dry and well ventilated room, protected against dust and direct sun rays and at temperatures between + 10°C and +30 °C. Under these conditions, the adhesive tapes could be stored a minimum of 12 months. Rolls should be stored flat on the slit edge and in their original packaging.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.