

## General description

The **GT-M1 resilient mattress** is made for duct crossing of walls. The GT-M1 is composed of a closed cell reticulated polyethylene foam with fire resistance Euroclasse B S2 d0 (equivalent to M1). There is an adhesive layer covered by a PE silicone protector film. Used for circular and rectangular ducts crossing walls. Insulating and separating ducts in the crossing with walls will not only reduce vibration, but also prevent oxidation.



For indoor use only.

## Technical specification

<b>Material</b>	Reticulated polyethylene foam
<b>Adhesive</b>	Rubber based hot melt
<b>Density</b>	29 kg / cubic meter
<b>Holding temperature</b>	-40°C to +80°C (-40°F to 176°F)
<b>Application temperature</b>	+15°C to +25°C (59°F to 77°F)
<b>Storage temperature</b>	+10°C to +25°C (50°F to 77°F)
<b>Compression strength</b>	88 kPa at 50% compression
<b>Resistance to water</b>	Good
<b>Thickness</b>	5 mm (3/16")
<b>Width</b>	220 mm (9")
<b>Length</b>	25 m (82 ft)
<b>Color</b>	Grey

*\*The values listed are ultimate averages achieved under standard laboratory conditions. These results are given only as a guide and not as a warranty. An appropriate safety factor must be determined for the designed purpose.*

## Application

Before application of the adhesive foam, the surface should be clean and dry, free of dust, grease, oil and any other loose matter. Remove the protector film on the adhesive side and apply on the duct. During application, make sure to apply a uniform pressure on it.